

PRODUCT NO. 2995

DOTLUX Driver not dimmable 3W Suitable only for Art.No.: 2775



to the product page

- Glare-free luminaire design especially for hotels and restaurants
- Driver and module individually replaceable with lockable quick-connect system
- Maintenance-friendly, modular system components
- Natural color perception thanks to extra high CRI value > 92

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.03	INPUT VOLTAGE	176 - 240 V AC/DC
POWER CONSUMPTION IN WATTS	3	OUTPUT CURRENT IN A	0,08
		INRUSH CURRENT IN A	0
		PROTECTION CLASS	II
		SUITED FOR EMERGENCY LIGHTING	yes
		OUTPUT VOLTAGE	32 DC
		INPUT VOLTAGE SPAN	180-250 V AC
		WARRANTY IN YEARS	3
		SUITED FOR EMERGENCY POWER	-
		INPUT VOLTAGE RANGE LUMINAIRE	180-250 V AC
		ETIM GRUPPEN-ID	EC002710
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	No

Dimensions

length: 74mm
width: 38mm
height: 25mm

DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
SUITABLE FOR EMERGENCY LIGHTING	Yes
MODEL	-
SUITABLE FOR OUTDOOR USE	No
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany