


PRODUCT NO. 3422

DOTLUX LED luminaire MULTIsun 8W 2000-2800K Sunset dimming (without decorative screen)



to the product page

- Flexible: Design your luminaire yourself and order luminaire and bezel separately according to your desired combination
- Screwless installation: Strain relief and connection terminal on the enclosed ballast via push-clamp technology - Multiple MULTIsun can be wired through
- SUNSETdimming for atmospheric and cozy lighting design
- Including phase dimming/ dimmable power supply unit (130 x 25 x 45 mm)
- This luminaire can be upgraded for use as emergency lighting.
(The battery kit accessories are required)

SUCCESSION ARTICLE	5245-030036
WEIGHT IN KG	0.3
POWER CONSUMPTION IN WATTS	8
NET LUMINOUS FLUX IN LUMENS	500
LUMEN PER WATT	63

Dimensions

height: 44mm
diameter: 80mm

BEAM ANGLE	38°
PROTECTION CLASS (IP)	IP65
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 40.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	2000-2800
COLOR-RENDERING-INDEX	CRI > 82
INRUSH CURRENT IN A	0
LUMEN PER WATT	63
PROTECTION CLASS	III
HOUSING COLOUR	black
SWITCH CYCLES	> 80.000
INSTALLATION OPENING DIAMETER IN MM	68
INPUT VOLTAGE SPAN	220-240 V AC
WARRANTY IN YEARS	7
INPUT VOLTAGE RANGE LUMINAIRE	220-240 V AC
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC001744
MATERIAL COVER	Glass transparent
DIMMING MAINS VOLTAGE MODULATION	Yes
DIMMING PHASE CUT-OFF	Yes
NO DIM FUNCTION	No

COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
EMERGENCY POWER SUPPLY INTEGRATED	No
DIMMING PHASE CUT-ON	Yes
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany
LED-BETRIEBSSTROM IN MA	350
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	G
BEAM ANGLE ADJUSTABLE	No
COLOUR OF LIGHT ADJUSTABLE	Continuously variable