PRODUCT NO. 1808-140120

DOTLUX LED-Panel FLATugr 620x620mm 40W 4000K UGR<19 Rahmen weiß (Lieferung ohne Netzteil)





to the product page

- Microprisma-Diffusor ermöglicht eine blendfreie, homogene und schattenfreie Lichtverteilung
- Ermüdungsfreies Arbeiten durch flimmerfreies Licht (= UGR<19 für Bildschirmarbeitsplätze)
- Bessere Kontrastwiedergabe bei sehr guter Farbwiedergabe und konstanter Farbtemperatur (3-Step MacAdam Binning)
- Hohe Anzahl an niedrig bestromten LEDs garantieren eine lange Lebensdauer der LED und in der Folge geringe Wartungskosten!
- Weißer, pulverbeschichteter Rahmen & Anschlusskabel mit Steckverbinder

SUCCESSION ARTICLE	1808-0FW120
PREDECESSOR ARTICLE	1808-1
WEIGHT IN KG	3.3
POWER CONSUMPTION IN WATTS	30/40
NET LUMINOUS FLUX IN LUMENS	3200/3900

Dimensions

length: 620mm
width: 620mm
height: 10mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP40
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 83
GLARE-FREE	UGR < 19
SWITCH CYCLES	> 100.000
WARRANTY IN YEARS	7
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
DIMMING 1-10 V	Yes
DIMMING DALI	Yes
DIMMING DMX	Yes
DIMMING LINESWITCH	Yes
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	Yes
DIMMING MAINS VOLTAGE MODULATION	Yes
DIMMING PHASE CUT-OFF	Yes
DIMMING PROGRAMMABLE	Yes
DIMMING RF	Yes
DIMMING ZIGBEE	Yes
DIMMING WITH PUSH-BUTTON	Yes

DIMMING DEPENDING ON CONTROL GEAR	Yes
DIMMING DALI-2	Yes
DIMMING PHASE CUT-ON	Yes