


PRODUCT NO. 1987-3

DOTLUX LINEAplus LED trunking system 1500mm through-wired blind unit



to the product page

- Quick-release fasteners for all connections
- Tool-free mounting rail with integrated through-wiring
- Luminaire insert with flexible phase selection (for non-dimmable version)
- Optimized transmittance of the lens
- Perfect cooling of the LED module thanks to aluminum core board
- High luminous efficacy thanks to optimized profile design
- Easily replaceable light unit
- Long service life thanks to oversized cooling
- Future-proof with replaceable LED module and separate driver
- Suitable for central battery (only DALI article no. 2811-3)

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP40
WEIGHT IN KG	4.6	LIGHT COLOR	-
		COLOR TEMPERATURE IN KELVIN	-
		INRUSH CURRENT IN A	0
		HOUSING COLOUR	white
		WARRANTY IN YEARS	7
Dimensions		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
length: 1510mm		ETIM GRUPPEN-ID	EC002892
width: 108mm		MATERIAL COVER	Plastic matt/satinized
height: 60mm		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	No
		DIMMING SINE WAVE REDUCTION	No

DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	-
COLOUR OF LIGHT ADJUSTABLE	No