PRODUCT NO. 3642-050120

DOTLUX LED hall floodlight LIGHTSHOWERevo 110W 5000K dimmable DALI Made in Germany



to the product page

- Rated current of the LEDs is only 38% of the max. current, resulting in extremely high efficiency and above-average life >100,000 h
- Pressure equalization valve extends seal life and prevents condensation inside the luminaire
- Glare control UGR typically <25
- 3-Step MacAdam binning guarantees consistent color temperature
- Aluminum core board for perfect thermal management
- High quality Meanwell® industrial power supply with 6 KV overvoltage protection
- DALI dimmable
- Intelligent, maintenance-friendly product design
- Suitable for central battery
- Highest efficiency due to 4 mm toughened safety glass \"Ultra Clear
- The D mark of this luminaire with limited surface temperature is a basic requirement for luminaires in fire hazardous locations (DIN EN 60598-2-24, VDE 0711-2-24)
- Sustainable product design due to easily replaceable components

SUCCESSION ARTICLE	-
WEIGHT IN KG	5.97
POWER CONSUMPTION IN WATTS	110
NET LUMINOUS FLUX IN LUMENS	18900
LUMEN PER WATT	172

Dimensions

length: 380mm
width: 380mm
height: 120mm
diameter: 380mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP67
LIGHT COLOR	white
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 80.000 h at 60°C
COLOR TEMPERATURE IN KELVIN	5000
COLOR-RENDERING-INDEX	CRI > 85
POWER FACTOR	0,97
INRUSH CURRENT IN A	0
IK PROTECTION	IK08
LUMEN PER WATT	172
PROTECTION CLASS	I
VOLTAGE TYPE	AC/DC
HOUSING COLOUR	gray
SWITCH CYCLES	> 160.000
INPUT VOLTAGE SPAN	100-305 V AC / 142-431 V DC
WARRANTY IN YEARS	7
L80/B10	80000
SUITABLE FOR SURFACE MOUNTING	Yes
SUITABLE FOR MOUNTING	No
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	100-305 V AC / 142-431 V DC
ASSORTMENT	Highline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	80000

ETIM GRUPPEN-ID	EC001744
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	No
SUITABLE FOR SUSPENDED MOUNTING	Yes
SUITABLE FOR CEILING MOUNTING	Yes
SUITABLE FOR NUMBER OF LIGHT SOURCES	1
LAMP HOLDER	-
MATERIAL COVER	Glass transparent
TYPE OF CONTROL GEAR	LED operating device voltage-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	Yes
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	Yes
NO DIM FUNCTION	No
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK08
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	Yes
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
CONNECTION TYPE	Cable
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR LOW VOLTAGE CABLE SYSTEM	Yes
SUITABLE FOR CLAMP-MOUNTING	No
SUITABLE FOR LIGHT-TRACK MOUNTING	No
SUITABLE FOR PEDESTAL/FLOOR MOUNTING	No
SUITABLE FOR TRAVERSE MOUNTING	No

EXCHANGEABLE CONTROL GEAR	Yes
SUITABLE FOR LAMP POWER IN W	110
LAMP TYPE	LED
EMERGENCY POWER SUPPLY INTEGRATED	No
SURFACE BRUSHED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	B
LIGHT OUTLET	Direct
TYPE OF WIRING	Suitable for through wiring
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
ADJUSTABILITY	Rotatable
LIGHT SHARING	Symmetric
SURFACE PROTECTION	Powder coating
REFLECTOR	None
LIGHT DISTRIBUTOR	None
BEAM ANGLE	Extreme wide beam >80°