

PRODUCT NO. 3666-060120

**DOTLUX LED Battery Spotlight WORKERmini 20W 6500K 7.4V**



to the product page

- Adjustable, glare-free light surfaces for homogeneous illumination with snap-in function
- Extremely compact, impact-resistant (IK08) and splash-proof (IP65) plastic housing
- Ergonomic carrying handle with integrated metal tripod mount
- Dimmable in three brightness levels with battery charge indicator
  - 30% light output = 9 hours
  - 50% light output = 6 hours
  - 100% light output = 3 hours (charging time max. 5 hours)
- Incl. charging cable for car/truck 12/24V and 220 V
- Inexpensive, replaceable, integrated lithium-ion battery
- Continuous operation via 220 V charging cable at full brightness level possible

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3026-160120
WEIGHT IN KG	1.58
POWER CONSUMPTION IN WATTS	20
NET LUMINOUS FLUX IN LUMENS	1900
LUMEN PER WATT	95

Dimensions

length: 324mm  
width: 180mm  
height: 90mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP65
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 40.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	6500
COLOR-RENDERING-INDEX	CRI > 82
INRUSH CURRENT IN A	0
IK PROTECTION	IK07
LUMEN PER WATT	95
PROTECTION CLASS	III
HOUSING COLOUR	multicoloured
SWITCH CYCLES	> 80.000
WARRANTY IN YEARS	3
DIMMING WITHOUT DIMMER	yes
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC001744
IMPACT STRENGTH	IK07
SUITABLE FOR LAMP POWER IN W	18
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	E