

PRODUCT NO. 3283-040135

DOTLUX LED street light BELUGAmini 73W 4000K SKI without pole mount



to the product page

- Protection class I with separate overvoltage protection (10,000 V)
- Variety of adapters enables mounting on all pole diameters
- The multilayer lens optics with CREE® LEDs enable uniform light distribution
- Solid cast aluminum housing in RAL 7022 with impact resistance class IK09 and smooth surface
- Highly efficient PHILIPS® LED driver ensures low maintenance costs
- Future-oriented module design with innovative cooling system
- Easy installation and tool-free maintenance
- Integrated pressure equalization valve

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3283 2409 2408-1
WEIGHT IN KG	5.55
POWER CONSUMPTION IN WATTS	max. 73
NET LUMINOUS FLUX IN LUMENS	8760
LUMEN PER WATT	120

Dimensions

length: 520mm
width: 300mm
height: 130mm

BEAM ANGLE	135°/50°
PROTECTION CLASS (IP)	IP66
LIGHT COLOR	white
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 80.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 80
MAST SUPPORT	depending on adapter
INRUSH CURRENT IN A	0
LUMEN PER WATT	120
PROTECTION CLASS	I
HOUSING COLOUR	gray
SWITCH CYCLES	> 160.000
OVERVOLTAGE PROTECTION	up to 10000 V
INPUT VOLTAGE SPAN	90-264 V AC
WARRANTY IN YEARS	7
INPUT VOLTAGE RANGE LUMINAIRE	90-264 V AC
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC000062
MATERIAL COVER	Glass transparent
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No

DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	D