

PRODUCT NO. 2672-030200

DOTLUX LED street lamp RETROFIT E40 33W 3000K rotatable base



to the product page

- Optimally arranged LEDs enable uniform light distribution
- Light control through rotatable base (with latching function)
- Light efficiency of up to 150 lm / W due to the use of high-quality certified LEDs
- A low beam angle of approx. 200° optimizes the use in residential areas

ENERGY

DOTLUX

2672-030200

A

B

C

D

E

F

G

D

33

kWh/1000h

2019/2015

SUCCESION ARTICLE	-
WEIGHT IN KG	0.465
POWER CONSUMPTION IN WATTS	33
NET LUMINOUS FLUX IN LUMENS	5150

Dimensions

height: 210mm  
diameter: 90mm

BEAM ANGLE	200°
PROTECTION CLASS (IP)	IP40
LIGHT COLOR	white
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 35.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 80
INRUSH CURRENT IN A	0
SUITED FOR EMERGENCY LIGHTING	yes
SWITCH CYCLES	> 100.000
INPUT VOLTAGE SPAN	85-265 V AC / 140-387 V DC
WARRANTY IN YEARS	5
L80/B10	34000
INPUT VOLTAGE RANGE LUMINAIRE	85-265 V AC / 140-387 V DC
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	D
LIFETIME L80/B10 AT 25°C	34000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	68000
ETIM GRUPPEN-ID	EC000062
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No

<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	Yes
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	68000
<b>LIFETIME L90/B10 AT 25°C</b>	17000
<b>PULSE DURATION IN µS</b>	0
<b>LIFETIME L90/B50 AT 25°C</b>	22667
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	-