

PRODUCT NO. 3842-040090

DOTLUX LED downlight CIRCLEugr 25W 3000/4000/5700K COLORselect



to the product page

- \"COLORselect\": 3 light colors in one luminaire. The right light color can be set for every application environment.
 1. Warm white 3,000 K: Hotel, store, wellness/spa areas, home & living.
 2. Neutral white 4,000 K: Office, gastronomy, industry, sanitary, retirement homes and hospitals
 3. Daylight white 5,700 K: Industry, conference rooms, educational institutions, office
- Glare-free luminaire design (UGR < 19)
- Facetted multi-reflector provides uniform illumination
- Tool-free terminal connection (through-wirable with integrated strain relief)
- Splash-proof housing design (IP 54 front side)
- SmartCooling: room-side heat dissipation via aluminum reflector
- Distance-free mounting possible
- Suitable for central battery

SUCCESSION ARTICLE	-	BEAM ANGLE	90°
WEIGHT IN KG	0.57	PROTECTION CLASS (IP)	other Front IP54 / rear IP20
POWER CONSUMPTION IN WATTS	25	LIGHT COLOR	multicoloured
NET LUMINOUS FLUX IN LUMENS	max. 2875	INPUT VOLTAGE	176 - 240 V AC/DC
LUMEN PER WATT	max. 115	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000/4000/5700
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,9
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK06
		LUMEN PER WATT	max. 115
		PROTECTION CLASS	II
		VOLTAGE TYPE	AC/DC
		HOUSING COLOUR	white
		SUITED FOR EMERGENCY LIGHTING	yes
		GLARE-FREE	UGR < 19
		SWITCH CYCLES	> 100.000
		FOOD-READY	Yes
		INSTALLATION OPENING WIDTH IN MM	0
		INSTALLATION OPENING DIAMETER IN MM	200-210
		INSTALLATION OPENING LENGHT IN MM	0
		WARRANTY IN YEARS	5
		L80/B10	50000
		SUITABLE FOR SURFACE MOUNTING	No
		SUITABLE FOR MOUNTING	Yes

Dimensions

height: 98mm
diameter: 228mm

DIMMING WITHOUT DIMMER	No
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	50000
ETIM GRUPPEN-ID	EC001744
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	No
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	Yes
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK06
SUITABLE FOR EMERGENCY LIGHTING	Yes
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
OPERATION BY BLUETOOTH	No
SUITABLE FOR LOW VOLTAGE CABLE SYSTEM	No
SUITABLE FOR CLAMP-MOUNTING	No
SUITABLE FOR LIGHT-TRACK MOUNTING	No
SUITABLE FOR PEDESTAL/FLOOR MOUNTING	No
SUITABLE FOR TRAVERSE MOUNTING	No
EXCHANGEABLE CONTROL GEAR	Yes
SUITABLE FOR LAMP POWER IN W	25
LAMP TYPE	LED
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	B

COLOUR OF LIGHT ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
REFLECTOR	Other
ADJUSTABILITY	Not adjustable
BEAM ANGLE	Extreme wide beam >80°
MATERIAL COVER	Without cover