

PRODUCT NO. 3843-040036

## DOTLUX LED Tracklight SLIMtrack 20-28W 4000K TRUE COLOR white



to the product page

- Vivid and high-contrast colors due to DOTLUX \"TRUE COLOR\" technology - always true colors
- Compatible with EUTRAC and almost all other 3-phase tracks
- Consistent light colors through 3-step MacAdam color sorting
- \"Stay-cool\" LED chip technology enables a modern, slim housing design with constant light output
- One item - 4 power levels adjustable (20W / 24W / 26W / 28W factory preset)
- High quality aluminum housing with powder coating (RAL9003)
- Toolless exchangeable high-power reflectors with bayonet lock
- Branded ballast from OSRAM
- Sustainable product design due to easily replaceable components

**SUCCESSION ARTICLE** 3845-199036

**WEIGHT IN KG** 1.17

**POWER CONSUMPTION IN WATTS** max. 28

**NET LUMINOUS FLUX IN LUMENS** max. 2670

**LUMEN PER WATT** 95

### Dimensions

**length:** 300mm

**diameter:** 85mm

<b>BEAM ANGLE</b>	36°
<b>PROTECTION CLASS (IP)</b>	IP20
<b>LIGHT COLOR</b>	white
<b>INPUT VOLTAGE</b>	220 - 240 V AC
<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
<b>COLOR TEMPERATURE IN KELVIN</b>	4000
<b>COLOR-RENDERING-INDEX</b>	CRI > 95 TRUECOLOR
<b>POWER FACTOR</b>	0,96
<b>INRUSH CURRENT IN A</b>	0
<b>IK PROTECTION</b>	IK06
<b>LUMEN PER WATT</b>	95
<b>PROTECTION CLASS</b>	II
<b>VOLTAGE TYPE</b>	AC
<b>HOUSING COLOUR</b>	white
<b>GLARE-FREE</b>	UGR < 19
<b>INSTALLATION OPENING WIDTH IN MM</b>	85
<b>INSTALLATION OPENING DIAMETER IN MM</b>	78
<b>INSTALLATION OPENING LENGHT IN MM</b>	135
<b>INPUT VOLTAGE SPAN</b>	220-240 V AC
<b>WARRANTY IN YEARS</b>	5
<b>RATED CURRENT</b>	0.16
<b>SIMILAR TO RAL-COLOUR</b>	9003
<b>SUITABLE FOR SURFACE MOUNTING</b>	No
<b>SUITABLE FOR MOUNTING</b>	No
<b>DIMMING WITHOUT DIMMER</b>	No

INPUT VOLTAGE RANGE LUMINAIRE	220-240 V AC
ASSORTMENT	Highline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	50000
ETIM GRUPPEN-ID	EC001744
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	No
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	Yes
SUITABLE FOR NUMBER OF LIGHT SOURCES	1
LAMP HOLDER	-
MATERIAL COVER	Plastic matt/satinized
WITH CONTROL GEAR	No
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
LIGHT DISTRIBUTOR	Reflector
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
DEGREE OF PROTECTION (NEMA)	1
IMPACT STRENGTH	IK06
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	Yes
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	650 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	Yes
TYPE OF WIRING	Through wiring included
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
COMPATIBLE WITH CASAMBI	No

COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR LOW VOLTAGE CABLE SYSTEM	No
SUITABLE FOR CLAMP-MOUNTING	No
SUITABLE FOR LIGHT-TRACK MOUNTING	Yes
SUITABLE FOR PEDESTAL/FLOOR MOUNTING	No
SUITABLE FOR TRAVERSE MOUNTING	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	-
LAMP TYPE	LED exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
SURFACE BRUSHED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	50000
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
DREH- /SCHWENKBAR	355° / 85°
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	E
LIGHT OUTLET	Direct
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
LIGHT SHARING	Symmetric
ADJUSTABILITY	Rotating and swivelling
SURFACE PROTECTION	Powder coating
BEAM ANGLE	Medium beam 21-40°
REFLECTOR	Other
TYPE OF CONTROL GEAR	Not required
CONNECTION TYPE	Solder