

PRODUCT NO. 3843-050036

DOTLUX LED Tracklight SLIMtrack 20-28W 5000K TRUE COLOR white



to the product page

- Vivid and high-contrast colors due to DOTLUX \"TRUE COLOR\" technology - always true colors
- Compatible with EUTRAC and almost all other 3-phase tracks
- Consistent light colors through 3-step MacAdam color sorting
- \"Stay-cool\" LED chip technology enables a modern, slim housing design with constant light output
- One item - 4 power levels adjustable (20W / 24W / 26W / 28W factory preset)
- High quality aluminum housing with powder coating (RAL9003)
- Toolless exchangeable high-power reflectors with bayonet lock
- Branded ballast from OSRAM
- Sustainable product design due to easily replaceable components

SUCCESSION ARTICLE 3843-199036

WEIGHT IN KG 1.17

POWER CONSUMPTION IN WATTS max. 28

NET LUMINOUS FLUX IN LUMENS max. 2670

LUMEN PER WATT 95

Dimensions

length: 312mm

diameter: 85mm

| | |
|--|--------------------------|
| BEAM ANGLE | 36° |
| PROTECTION CLASS (IP) | IP20 |
| LIGHT COLOR | white |
| INPUT VOLTAGE | 220 - 240 V AC |
| SERVICE LIFE | approx. 50.000 h at 25°C |
| COLOR TEMPERATURE IN KELVIN | 5000 |
| COLOR-RENDERING-INDEX | CRI > 95 TRUECOLOR |
| POWER FACTOR | 0,96 |
| INRUSH CURRENT IN A | 0 |
| IK PROTECTION | IK06 |
| LUMEN PER WATT | 95 |
| PROTECTION CLASS | II |
| VOLTAGE TYPE | AC |
| HOUSING COLOUR | white |
| GLARE-FREE | UGR < 19 |
| INSTALLATION OPENING WIDTH IN MM | 85 |
| INSTALLATION OPENING DIAMETER IN MM | 135 |
| INSTALLATION OPENING LENGHT IN MM | 78 |
| INPUT VOLTAGE SPAN | 220-240 V AC |
| WARRANTY IN YEARS | 5 |
| RATED CURRENT | 0.16 |
| SIMILAR TO RAL-COLOUR | 9003 |
| SUITABLE FOR SURFACE MOUNTING | No |
| SUITABLE FOR MOUNTING | No |
| DIMMING WITHOUT DIMMER | No |

| | |
|---|-------------------------|
| INPUT VOLTAGE RANGE LUMINAIRE | 220-240 V AC |
| ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 | not required |
| LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C | 50000 |
| ETIM GRUPPEN-ID | EC001744 |
| WITH ILLUMINANT | Yes |
| SUITABLE FOR WALL MOUNTING | No |
| SUITABLE FOR SUSPENDED MOUNTING | No |
| SUITABLE FOR CEILING MOUNTING | No |
| SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1 | Yes |
| SUITABLE FOR NUMBER OF LIGHT SOURCES | 1 |
| LAMP HOLDER | - |
| MATERIAL COVER | Plastic matt/satinized |
| WITH CONTROL GEAR | No |
| DIMMING 0-10 V | No |
| DIMMING 1-10 V | No |
| DIMMING DALI | No |
| DIMMING DMX | No |
| DIMMING DSI | No |
| DIMMING POTENTIOMETER (INTEGRATED) | No |
| DIMMING LINESWITCH | No |
| DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | No |
| DIMMING MAINS VOLTAGE MODULATION | No |
| DIMMING PHASE CUT-OFF | No |
| DIMMING PROGRAMMABLE | No |
| DIMMING RF | No |
| DIMMING SINE WAVE REDUCTION | No |
| DIMMING TOUCH AND DIM | No |
| DIMMING ZIGBEE | No |
| DIMMING WITH PUSH-BUTTON | No |
| DIMMING DEPENDING ON CONTROL GEAR | No |
| NO DIM FUNCTION | Yes |
| LIGHT DISTRIBUTOR | Reflector |
| COLOUR CONSISTENCY (MCADAM ELLIPSE) | SDCM6 |
| DEGREE OF PROTECTION (NEMA) | 1 |
| IMPACT STRENGTH | IK06 |
| LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24 | Yes |
| WITH MOVEMENT SENSOR | No |
| WITH LIGHT SENSOR | No |
| COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE | No |
| FILAMENT TEST ACCORDING TO IEC 60695-2-11 | 650 °C - 30 s |
| CONSTANT LIGHT OUTPUT (CLO) | Yes |
| TYPE OF WIRING | Through wiring included |
| PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471 | RG1 |
| COMPATIBLE WITH CASAMBI | No |
| COMPATIBLE WITH APPLE HOMEKIT | No |

| | |
|--|--------------------------|
| COMPATIBLE WITH GOOGLE ASSISTANT | No |
| COMPATIBLE WITH AMAZON ALEXA | No |
| IFTTT SUPPORT AVAILABLE | No |
| SUITABLE FOR LOW VOLTAGE CABLE SYSTEM | No |
| SUITABLE FOR CLAMP-MOUNTING | No |
| SUITABLE FOR LIGHT-TRACK MOUNTING | Yes |
| SUITABLE FOR PEDESTAL/FLOOR MOUNTING | No |
| SUITABLE FOR TRAVERSE MOUNTING | No |
| EXCHANGEABLE CONTROL GEAR | No |
| SUITABLE FOR LAMP POWER IN W | - |
| LAMP TYPE | LED exchangeable |
| EMERGENCY POWER SUPPLY INTEGRATED | No |
| SURFACE BRUSHED | No |
| DIMMING DALI-2 | No |
| DIMMING PHASE CUT-ON | No |
| DIMMING GPRS | No |
| LIFETIME L70/B50 AT 25°C | 50000 |
| PULSE DURATION IN µS | 0 |
| BEG FUNDING | Only relevant in Germany |
| DREH- /SCHWENKBAR | 355° / 85° |
| ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE | E |
| LIGHT OUTLET | Direct |
| COLOUR OF LIGHT ADJUSTABLE | No |
| LUMINOUS FLUX ADJUSTABLE | No |
| BEAM ANGLE ADJUSTABLE | No |
| LIGHT SHARING | Symmetric |
| ADJUSTABILITY | Rotating and swivelling |
| SURFACE PROTECTION | Powder coating |
| BEAM ANGLE | Medium beam 21-40° |
| REFLECTOR | Other |
| TYPE OF CONTROL GEAR | Not required |
| CONNECTION TYPE | Solder |