

PRODUCT NO. 1808-350120

DOTLUX LED panel FLATugr 620x620mm 40W 5000K UGR<19 frame white (0-10V dimmable power supply unit included) set of 2



to the product page

Set of 2 consisting of 2x panel and 2x 0-10V dimmable power supply units

Microprism diffuser enables glare-free, homogeneous and shadow-free light distribution
Fatigue-free working thanks to flicker-free light (= UGR < 19 for VDU workstations)
Better contrast rendition with very good color rendering
and constant color temperature (3-step MacAdam binning)
High number of low-current LEDs guarantee a long LED service life
LED service life and consequently low maintenance costs!
White, powder-coated frame & connection cable with plug connector

SUCCESSION ARTICLE	1808-3FW090	BEAM ANGLE	120°
WEIGHT IN KG	3.3	PROTECTION CLASS (IP)	IP40
POWER CONSUMPTION IN WATTS	40	INPUT VOLTAGE	220 - 240 V AC
NET LUMINOUS FLUX IN LUMENS	3900	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	5000
		COLOR-RENDERING-INDEX	CRI > 83
		GLARE-FREE	UGR < 19
		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	7
		ETIM GRUPPEN-ID	EC002892
		DIMMING 1-10 V	Yes
		DIMMING DALI	Yes
		DIMMING DMX	Yes
		DIMMING LINESWITCH	Yes
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	Yes
		DIMMING MAINS VOLTAGE MODULATION	Yes
		DIMMING PHASE CUT-OFF	Yes
		DIMMING PROGRAMMABLE	Yes
		DIMMING RF	Yes
		DIMMING ZIGBEE	Yes
		DIMMING WITH PUSH-BUTTON	Yes
		DIMMING DEPENDING ON CONTROL GEAR	Yes
		DIMMING DALI-2	Yes

Dimensions

length: 620mm
width: 620mm
height: 10mm

DIMMING PHASE CUT-ON

Yes