

PRODUCT NO. 4234-040160

**DOTLUX LED strip light system LINEAclick 25W 4000K wide beam Made in Germany**



to the product page

- Continued use of your existing mounting rail system
- Mounting without mechanical intervention in the mounting rail system with heat-resistant neodymium
  - magnetic holders incl. safety rope
- Independent, integrated cable system with quick connectors
- Optimized transmittance of the patented LINEAclick lens from DOTLUX®
- Shadow-free light distribution thanks to innovative lens design
- Perfect cooling of the LED module thanks to aluminum core board
- LM80 certified LEDs with 40% current consumption
- Suitable for central battery (only DALI article no. 2814-350045 and 2813-450160)

SUCCESSION ARTICLE	-	BEAM ANGLE	160°
WEIGHT IN KG	1.955	PROTECTION CLASS (IP)	IP40
POWER CONSUMPTION IN WATTS	25	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	4175	INPUT VOLTAGE	176 - 240 V AC/DC
LUMEN PER WATT	167	Service life	
		COLOR TEMPERATURE IN KELVIN	4000
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,91
		INRUSH CURRENT IN A	1290
		LUMEN PER WATT	167
		PROTECTION CLASS	I
		VOLTAGE TYPE	AC
		HOUSING COLOUR	Aluminium
		SUITED FOR EMERGENCY LIGHTING	No
		SWITCH CYCLES	> 200.000
		INPUT VOLTAGE SPAN	198-264 V AC / 176-280 V DC
		WARRANTY IN YEARS	7
		L80/B10	100000
		RATED CURRENT	1.5
		SUITABLE FOR SURFACE MOUNTING	Yes
		SUITABLE FOR MOUNTING	No
		INPUT VOLTAGE RANGE LUMINAIRE	198-264 V AC / 176-280 V DC
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	100000

**Dimensions**

length: 1530mm  
width: 73mm  
height: 61mm

ETIM GRUPPEN-ID	EC002892
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	No
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	Yes
SUITABLE FOR LIGHT LINE CONFIGURATION	Yes
LAMP HOLDER	-
MATERIAL COVER	Plastic matt/satinized
TYPE OF GRID	-
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	Yes
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	Yes
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
TYPE OF WIRING	Through wiring included
CONNECTION TYPE	Bus
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	Yes
SUITABLE FOR LAMP POWER IN W	25
LAMP TYPE	LED

<b>EMERGENCY POWER SUPPLY INTEGRATED</b>	No
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN <math>\mu</math>S</b>	0
<b>BEG FUNDING</b>	only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	C
<b>LIGHT OUTLET</b>	Direct
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>LUMINOUS FLUX ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>LIGHT SHARING</b>	Symmetric
<b>LIGHT DISTRIBUTOR</b>	Other
<b>SURFACE PROTECTION HOUSING</b>	Other
<b>BEAM ANGLE</b>	Extreme wide beam >80°