

PRODUCT NO. 1964-0601605


DOTLUX LED module ADplus 0,72W 12V 160° IP65 6000K 20pcs chain



to the product page

- Input voltage: 12 V DC
- LED module ADplus is delivered ready wired as a chain of 20 modules!
- Technically, up to 2 chains (à 20 modules) can be wired in series.
- A parallel connection of several chains is possible for the uniform illumination of larger larger areas without any problems.


TIP:In order to extend the maintenance cycle of the power supply it is recommended to design the power supply with approx. 20% more power than required.
than required.



DOTLUX
1964-0601605

A	
B	
C	
D	
E	
F	
G	

1
kWh/1000h



2019/2015

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	1964
WEIGHT IN KG	1.35
NET LUMINOUS FLUX IN LUMENS	60
LUMEN PER WATT	86

Dimensions

length: 70mm
width: 15mm
height: 7mm

BEAM ANGLE	160°
PROTECTION CLASS (IP)	IP65
TEMPERATURE RANGE	-40°C to +40°C
LIGHT COLOR	white
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	6000
COLOR-RENDERING-INDEX	CRI > 80
LUMEN PER WATT	86
PROTECTION CLASS	III
SELF-STICKING	yes
SWITCH CYCLES	> 100.000
INPUT VOLTAGE SPAN	12 V DC
WARRANTY IN YEARS	5
INPUT VOLTAGE RANGE LUMINAIRE	12 V DC
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	G
ETIM GRUPPEN-ID	EC002706
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	-
COLOUR OF LIGHT ADJUSTABLE	No