

PRODUCT NO. 4252-24

LED power supply unit CV 24V DC 75W 3.15A IP67



to the product page

- The LED power supply units in an IP67 aluminum housing are used for LED and lighting applications.
- Overload protection by switching off
- Suitable for constant current and constant voltage

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP67
WEIGHT IN KG	0.674	INPUT VOLTAGE	176 - 240 V AC/DC
POWER CONSUMPTION IN WATTS	75	OUTPUT CURRENT IN A	3,15
		INRUSH CURRENT IN A	0
		TC TEMPERATURE IN °C	85
		OUTPUT VOLTAGE	24 DC
		INPUT VOLTAGE SPAN	100-305 V AC / 142-431 V DC
		INPUT VOLTAGE RANGE LUMINAIRE	100-305 V AC / 142-431 V DC
		ETIM GRUPPEN-ID	EC002710
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	No
		DIMMING SINE WAVE REDUCTION	No
		DIMMING TOUCH AND DIM	No
		DIMMING ZIGBEE	No

Dimensions

length: 243mm
width: 71mm
height: 37mm

DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany