

PRODUCT NO. 4253-24

LED power supply unit CV 24V DC 150W 6.25A IP67





to the product page



- Power supply unit in metal housing
- adjustable
- The power supply unit has temperature monitoring
- Overload protection through current limitation

| SUCCESSION ARTICLE | 5359 |
|----------------------------|------|
| WEIGHT IN KG | 0.85 |
| POWER CONSUMPTION IN WATTS | 150 |

Dimensions

length: 219mm width: 63mm height: 36mm

| PROTECTION CLASS (IP) | IP67 |
|--|-----------------------------|
| | 176 - 240 V AC/DC |
| | 6.25 |
| POWER FACTOR | 0.95 |
| INRUSH CURRENT IN A | о, <i>22</i> |
| | 90 |
| | 50 |
| | 24 DC |
| INPUT VOLTAGE SPAN | 100-305 V AC / 142-431 V DC |
| | 100-305 V AC / 142-431 V DC |
| | EC002710 |
| DIMMING 0-10 V | No |
| DIMMING 1-10 V | No |
| DIMMING DALI | No |
| DIMMING DMX | No |
| DIMMING DSI | No |
| DIMMING POTENTIOMETER (INTEGRATED) | No |
| DIMMING LINESWITCH | No |
| DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | No |
| DIMMING MAINS VOLTAGE MODULATION | No |
| DIMMING PHASE CUT-OFF | No |
| DIMMING PROGRAMMABLE | No |
| DIMMING RF | No |
| DIMMING SINE WAVE REDUCTION | No |
| DIMMING TOUCH AND DIM | No |
| | |



| DIMMING ZIGBEE | No |
|--------------------------|--------------------------|
| DIMMING WITH PUSH-BUTTON | No |
| NO DIM FUNCTION | Yes |
| DIMMING PHASE CUT-ON | No |
| DIMMING GPRS | No |
| PULSE DURATION IN µS | 0 |
| BEG FUNDING | Only relevant in Germany |
| | |