

PRODUCT NO. 4252-12

LED power supply CV 12V DC 60W 5A IP67



to the product page

- Power supply in aluminum housing
- Overload protection by shutdown
- IP67 protected housing
- not dimmable
- with open cable ends

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP67
WEIGHT IN KG	0.696	INPUT VOLTAGE	176 - 240 V AC/DC
POWER CONSUMPTION IN WATTS	60	OUTPUT CURRENT IN A	5
		POWER FACTOR	0,95
		INRUSH CURRENT IN A	0
		TC TEMPERATURE IN °C	85
Dimensions		OUTPUT VOLTAGE	12 DC
length: 180mm		INPUT VOLTAGE SPAN	100-305 V AC / 142-431 V DC
width: 63mm		INPUT VOLTAGE RANGE LUMINAIRE	100-305 V AC / 142-431 V DC
height: 36mm		ETIM GRUPPEN-ID	EC002710
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	No
		DIMMING SINE WAVE REDUCTION	No
		DIMMING TOUCH AND DIM	No

<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN <math>\mu</math>S</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany