

PRODUCT NO. 4255-24

LED power supply CV 24V/DC 240W 10A IP20 for DIN rail mounting



to the product page

- Switching power supply for DIN rail mounting
- LED display for DC OK.
- due to the closed design the screw terminals are protected against accidental contact
- overload protection by current limitation

SUCCESSION ARTICLE	-
WEIGHT IN KG	0.92
POWER CONSUMPTION IN WATTS	240

Dimensions

length: 114mm
width: 63mm
height: 125mm

INPUT VOLTAGE	176 - 240 V AC/DC
OUTPUT CURRENT IN A	10
POWER FACTOR	0,95
INRUSH CURRENT IN A	0
OUTPUT VOLTAGE	24 DC
INPUT VOLTAGE SPAN	90-264 V AC / 127-370 V DC
INPUT VOLTAGE RANGE LUMINAIRE	90-264 V AC / 127-370 V DC
ETIM GRUPPEN-ID	EC002710
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No

NO DIM FUNCTION	Yes
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany