

PRODUCT NO. 4323

DOTLUX Netzteil 150W 48V 3,13A CV+CC



the power supply supports constant current and constant voltage output in dual mode.

Thanks to the 91% high efficiency and fanless design, the series can operate under free air convection in the temperature range of -40°C to +90°C. IP65 protection class due to intelligent design and aluminum housing.

SUCCESSION ARTICLE	kein NF - Sortimenststraffung	PROTECTION CLASS (IP)	IP65
WEIGHT IN KG	0.87	FREQUENCY RANGE IN HZ	47-63
POWER CONSUMPTION IN WATTS	105	OUTPUT CURRENT IN A	3,13
		POWER FACTOR	0,97
		INRUSH CURRENT IN A	0
		PROTECTION CLASS	I
		OUTPUT VOLTAGE	48 DC
		INPUT VOLTAGE SPAN	100-305 V AC / 142-431 V DC
		WARRANTY IN YEARS	3
		INPUT VOLTAGE RANGE LUMINAIRE	100-305 V AC / 142-431 V DC
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	No

<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN <math>\mu</math>S</b>	0