

PRODUCT NO. 2786-227038-B-Ware

DOTLUX LED-Downlight CIRCLEmini 2700K 6,5W Housing: high-grade steel - very low installation depth - (B-Stock)









to the product page



- Perfect for renovations due to low installation depth and large coverage
- Driver and module individually replaceable with lockable quick plug-in connection
- Maintenance-friendly, modular system components
- Natural colour perception thanks to the extra high CRI value > 92
- This luminaire can be extended for use as emergency lighting. (The battery kit is required)

ATTENTION: Dust inclusions and slight scratches on the paintwork. Technically flawless.

 WEIGHT IN KG
 0.135

 POWER CONSUMPTION IN WATTS
 6,5

 CONSUMPTION (KWH/1000H)
 6,5

 NET LUMINOUS FLUX IN LUMENS
 max. 550

Dimensions

height: 31mm

diameter: 94mm

BEAM ANGLE 38°
PROTECTION CLASS (IP) IP20

SERVICE LIFE approx. 50.000 h at 25°C

COLOR TEMPERATURE IN KELVIN 2700

POWER SUPPLY Separate order

COLOR-RENDERING-INDEX CRI > 92

INRUSH CURRENT IN A

SWITCH CYCLES > 100.000
INSTALLATION OPENING DIAMETER IN

MM 68-88

WARRANTY IN YEARS

ENERGY EFFICIENCY CLASS

ACCORDING TO EU REGULATION not required 2019/2015

ETIM GRUPPEN-ID EC001744

DIMMING DEPENDING ON CONTROL

Voc

GEAR

GEAR

PULSE DURATION IN μS

DREH- /SCHWENKBAR swivelling +/-30° **ADJUSTABILITY** Swivelling