

PRODUCT NO. 3109-150120-B-Ware

LED-Feuchtraumleuchte MISTRALxtreme 1500mm 60W 5000K IP66



to the product page

<?xml:namespace prefix="o" />

- + Gehäuse komplett aus Aluminium und Glas, dadurch extrem witterungsbeständig und für den Außenbereich geeignet
- + Werkseitige 5-polige Durchverdrahtung ermöglicht eine schnelle Montage
- + Mikroprismatisches ESG-Glas für blendfreie Lichtverteilung (UGR < 19)
- + Montagezubehör mitgeliefert (Decken-/Wand- oder abgehängte Montage)
- + Montageklammern sind an der Leuchte frei positionierbar – vorhandene Befestigungspunkte an Decke und Wand können weiter genutzt werden
- + Metall-Kabelverschraubung und Metall-Abdeckung beiliegend
- + Schlagfestigkeit IK08
- + Geeignet für Zentralbatterie

| | |
|-----------------------------|------|
| WEIGHT IN KG | 4.8 |
| POWER CONSUMPTION IN WATTS | 60 |
| CONSUMPTION (KWH/1000H) | 60 |
| NET LUMINOUS FLUX IN LUMENS | 7800 |

| | |
|-------------------------------|--------------------------|
| BEAM ANGLE | 120° |
| PROTECTION CLASS (IP) | IP66 |
| INPUT VOLTAGE | 220 - 240 V AC |
| SERVICE LIFE | approx. 50.000 h at 25°C |
| COLOR TEMPERATURE IN KELVIN | 5000 |
| POWER SUPPLY | Integrated |
| COLOR-RENDERING-INDEX | CRI > 82 |
| IK PROTECTION | IK08 |
| SUITED FOR EMERGENCY LIGHTING | yes |
| EMERGENCY LIGHTING INTEGRATED | - |
| FIRE PROTECTION "D" | yes |
| GLARE-FREE | UGR < 19 |
| SUITABLE FOR THROUGH-WIRING | Yes |
| SWITCH CYCLES | > 80.000 |
| COVER MATERIAL | Safety-glass |
| INPUT VOLTAGE SPAN | 220-240 V AC |
| WARRANTY IN YEARS | 0 |
| HOUSING MATERIAL | Aluminium |
| SUITED FOR EMERGENCY POWER | - |
| INPUT VOLTAGE RANGE LUMINAIRE | 220-240 V AC |
| ETIM GRUPPEN-ID | EC002892 |
| DIMMING 0-10 V | No |
| DIMMING 1-10 V | No |
| DIMMING DALI | No |
| DIMMING DMX | No |
| DIMMING DSI | No |

Dimensions

length: 1540mm
width: 112mm
height: 89mm

| | |
|--|-------|
| DIMMING POTENTIOMETER (INTEGRATED) | No |
| DIMMING LINESWITCH | No |
| DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | No |
| DIMMING MAINS VOLTAGE MODULATION | No |
| DIMMING PHASE CUT-OFF | No |
| DIMMING PROGRAMMABLE | No |
| DIMMING RF | No |
| DIMMING SINE WAVE REDUCTION | No |
| DIMMING TOUCH AND DIM | No |
| DIMMING ZIGBEE | No |
| DIMMING WITH PUSH-BUTTON | No |
| DIMMING DEPENDING ON CONTROL GEAR | No |
| NO DIM FUNCTION | Yes |
| IMPACT STRENGTH | IK08 |
| SUITABLE FOR EMERGENCY LIGHTING | Yes |
| EMERGENCY POWER SUPPLY INTEGRATED | Yes |
| DIMMING DALI-2 | No |
| DIMMING PHASE CUT-ON | No |
| DIMMING GPRS | No |
| OPTICS OF THE COVER | satin |