

PRODUCT NO. 3901-030360-B-Ware

DOTLUX LED light MOONBASE 18W 3000K



to the product page

Acrylic glass ring with microprint creates attractive lighting effects
Removable front cover enables easy mounting on ceiling and wall
Separately available cover caps offer the option of individualization
Suitable for central battery

WEIGHT IN KG	1.3
POWER CONSUMPTION IN WATTS	18
NET LUMINOUS FLUX IN LUMENS	1690

Dimensions

height: 46mm
diameter: 370mm

BEAM ANGLE	360°
PROTECTION CLASS (IP)	IP40
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 82
IK PROTECTION	IK05
PROTECTION CLASS	I
VOLTAGE TYPE	AC/DC
HOUSING COLOUR	white
GLARE-FREE	UGR < 25
SWITCH CYCLES	> 100.000
INPUT VOLTAGE SPAN	100-277 V AC
WARRANTY IN YEARS	0
INPUT VOLTAGE RANGE LUMINAIRE	100-277 V AC
ETIM GRUPPEN-ID	EC002892
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No

DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
IMPACT STRENGTH	IK05
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No