

PRODUCT NO. 4336

LED power supply CC 750mA 40W 30-50V incl. motion and daylight sensor



to the product page

- Three different functions of the high-frequency sensor possible:
  - On/Off function to 100% light intensity via sensor, then 0% light intensity.
  - On/Off function to 100% luminous intensity via sensor with adjustable afterglow duration/power
  - Permanent basic brightness (20% / 35% luminosity) with additional On/Off function to 100% luminosity via sensor with adjustable afterglow duration
- In addition, the following values are adjustable in steps:
  - Range (up to 10 m)
  - daylight sensor - light duration
  - Afterglow duration (none to continuous)
  - Afterglow power (10% / 25%)

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0	INPUT VOLTAGE	220 - 240 V AC
POWER CONSUMPTION IN WATTS	60	TC TEMPERATURE IN °C	50
		PROTECTION CLASS	II
		SUITED FOR EMERGENCY LIGHTING	No
		OUTPUT VOLTAGE	30 - 50 DC
		INPUT VOLTAGE SPAN	220-240 V AC
		DIMMING WITHOUT DIMMER	No
		INPUT VOLTAGE RANGE LUMINAIRE	220-240 V AC
		ETIM GRUPPEN-ID	EC002710
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	Yes
		DIMMING RF	No
		DIMMING TOUCH AND DIM	No
		DIMMING ZIGBEE	No

Dimensions

length: 125mm  
width: 35mm  
height: 21mm

<b>DIMMING WITH PUSH-BUTTON</b>	Yes
<b>NO DIM FUNCTION</b>	No
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	No
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>HOUSING</b>	Plastic housing
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>BEG FUNDING</b>	Only relevant in Germany