

PRODUCT NO. 4365-0FW090

DOTLUX LED luminaire CIRCLEugr-top 25W 3000/4000/5700K COLORselect white



to the product page

- Adjustable power: 15W, 20W or 25W selectable
- Ideal for office workplaces, as UGR value <19
- Tool-free terminal connection (through-wirable with integrated strain relief)
- Splash-proof housing design (IP 54 front)
- Suitable for central battery
- \\"COLORselect\\": 3 light colors in one luminaire. For every application environment the right light color can be set.
 1. Warm white 3,000 K: Hotel, store, wellness/spa areas, home & living
 2. Neutral white 4,000 K: Office, gastronomy, industry, sanitary, retirement homes and hospitals
 3. Daylight white 5,700 K: Industry, conference rooms, educational institutions, office

SUCCESSION ARTICLE	-	BEAM ANGLE	90°
WEIGHT IN KG	0.83	PROTECTION CLASS (IP)	IP54
POWER CONSUMPTION IN WATTS	15/20/25	LIGHT COLOR	multicoloured
NET LUMINOUS FLUX IN LUMENS	2890	INPUT VOLTAGE	176 - 240 V AC/DC
LUMEN PER WATT	max. 116	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000/4000/5700
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,9
Dimensions		INRUSH CURRENT IN A	0
height: 128mm		LUMEN PER WATT	max. 116
diameter: 210mm		PROTECTION CLASS	I
		VOLTAGE TYPE	AC/DC
		HOUSING COLOUR	white
		SUITED FOR EMERGENCY LIGHTING	yes
		GLARE-FREE	UGR < 19
		WARRANTY IN YEARS	5
		L80/B10	50000
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	50000
		LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	60000
		ETIM GRUPPEN-ID	EC001744
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No

DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
SUITABLE FOR EMERGENCY LIGHTING	Yes
COLOUR OF LIGHT ADJUSTABLE	Positions
LUMINOUS FLUX ADJUSTABLE	Positions
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	60000
LIFETIME L90/B10 AT 25°C	15000
PULSE DURATION IN µS	0
LIFETIME L90/B50 AT 25°C	20000
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	D
MATERIAL COVER	Without cover