

PRODUCT NO. 4366-0FW090

DOTLUX LED luminaire CIRCLEugr-top 25W 3000/4000/5700K COLORselect black



to the product page

- Adjustable power: 15W, 20W or 25W selectable
- Ideal for office workplaces, as UGR value <19
- Tool-free terminal connection (through-wirable with integrated strain relief)
- Splash-proof housing design (IP 54 front)
- Suitable for central battery
- \("COLORselect\)": 3 light colors in one luminaire. The right light color can be set for every application environment.
 1. Warm white 3,000 K: Hotel, store, wellness/spa areas, home & living
 2. Neutral white 4,000 K: Office, gastronomy, industry, sanitary, retirement homes and hospitals
 3. Daylight white 5,700 K: Industry, conference rooms, educational institutions, office

SUCCESSION ARTICLE	-	BEAM ANGLE	90°
WEIGHT IN KG	0.85	PROTECTION CLASS (IP)	IP54
POWER CONSUMPTION IN WATTS	15/20/25	LIGHT COLOR	multicoloured
NET LUMINOUS FLUX IN LUMENS	2890	INPUT VOLTAGE	176 - 240 V AC/DC
LUMEN PER WATT	116	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000/4000/5700
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,9
Dimensions		INRUSH CURRENT IN A	0
height: 128mm		LUMEN PER WATT	116
diameter: 210mm		PROTECTION CLASS	I
		VOLTAGE TYPE	AC/DC
		HOUSING COLOUR	black
		GLARE-FREE	UGR < 19
		WARRANTY IN YEARS	5
		L80/B10	50000
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	50000
		LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	60000
		ETIM GRUPPEN-ID	EC001744
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No

DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
COLOUR OF LIGHT ADJUSTABLE	Positions
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	60000
LIFETIME L90/B10 AT 25°C	15000
PULSE DURATION IN µs	0
LIFETIME L90/B50 AT 25°C	20000
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	D
MATERIAL COVER	Without cover