

PRODUCT NO. 3293-240180-DALI

## DOTLUX LED luminaire insert LINEAselect 1437mm 25-80W 4000K dimmable DALI 120°



to the product page

- Quick-release fasteners for all connections
- Tool-free mounting rail with integrated through-wiring
- Luminaire insert with flexible phase selection and power adjustment via DIP switch on the power supply unit
- Optimized transmittance of the diffusing lens
- Self-cooling LED module
- High luminous efficacy thanks to optimized profile design
- Easily replaceable light units with excellent price-performance ratio
- Long service life thanks to oversized cooling
- Suitable for central battery

Adjustable output thanks to POWERselect:

- 12300@ 78W
- 10900@ 70W
- 9400@ 59W
- 7850@ 47W
- 7200@ 43W
- 6100@ 37W
- 5250@ 32W
- 4300@ 26W

**SUCCESSION ARTICLE** -  
**PREDECESSOR ARTICLE** 3293-040180-DALI

**WEIGHT IN KG** 1.66  
**POWER CONSUMPTION IN WATTS** 25-80  
**NET LUMINOUS FLUX IN LUMENS** max.12300  
**LUMEN PER WATT** 158-165

### Dimensions

**length:** 1437mm  
**width:** 65mm  
**height:** 59mm

**BEAM ANGLE** 120°  
**PROTECTION CLASS (IP)** IP40  
**LIGHT COLOR** white  
**INPUT VOLTAGE** 186 - 240 AC/DC  
**SERVICE LIFE** approx. 50.000 h at 25°C  
**COLOR TEMPERATURE IN KELVIN** 4000  
**COLOR-RENDERING-INDEX** CRI > 83  
**POWER FACTOR** 0,98  
**INRUSH CURRENT IN A** 0  
**LUMEN PER WATT** 158-165  
**HOUSING COLOUR** white  
**SWITCH CYCLES** > 100.000  
**WARRANTY IN YEARS** 7  
**L80/B10** 75750  
**ASSORTMENT** Proline  
**ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015** not required  
**LIFETIME L80/B10 AT 25°C** 75750  
**LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C** 150000  
**ETIM GRUPPEN-ID** EC002892

<b>MATERIAL COVER</b>	Plastic matt/satinized
<b>DIMMING DALI</b>	Yes
<b>NO DIM FUNCTION</b>	No
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	150000
<b>LIFETIME L90/B10 AT 25°C</b>	37500
<b>PULSE DURATION IN µS</b>	0
<b>BEG FUNDING</b>	only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	B
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No