

PRODUCT NO. 4523-24

LED power supply CV 24V DC 0-20W 0-0,84A not dimmable IP20 ultra flat



to the product page

- Super flat power supply offers a solution for installations that require a compact design.
- Suitable for indoor LED lighting applications
- SELV compliant output
- flicker free design

SUCCESSION ARTICLE	-
WEIGHT IN KG	0.07
POWER CONSUMPTION IN WATTS	0-20

Dimensions

length: 17mm
width: 40mm
height: 14mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
POWER FACTOR	0,5
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	75
PROTECTION CLASS	II
OVERVOLTAGE PROTECTION	500 V
OUTPUT VOLTAGE	24 DC
INPUT VOLTAGE SPAN	198-264 V AC
WARRANTY IN YEARS	2
INPUT VOLTAGE RANGE LUMINAIRE	198-264 V AC
ETIM GRUPPEN-ID	EC002710
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No

DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany