

PRODUCT NO. 4526-24

LED power supply CV 24V DC 0-75W 0-3,1 A not dimmable IP20 ultra flat



- Flat power supply for modern LED lighting indoors
- Power supply complies with relevant EMC safety standards

SUCCESSION ARTICLE	-
WEIGHT IN KG	0.162
POWER CONSUMPTION IN WATTS	0-75

Dimensions

length: 298mm
width: 30mm
height: 17mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
Output current in A	
POWER FACTOR	0,95
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	90
PROTECTION CLASS	II
OVERVOLTAGE PROTECTION	1000 V
OUTPUT VOLTAGE	24 DC
INPUT VOLTAGE SPAN	198-264 V AC
WARRANTY IN YEARS	2
INPUT VOLTAGE RANGE LUMINAIRE	198-264 V AC
ETIM GRUPPEN-ID	EC002710
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No

DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany