

PRODUCT NO. 4558-030360

**DOTLUX LED bollard light WAY 20cm 7.5/15W 3000K**



PROLINE



to the product page

**Dotlux LED bollard light WAY 20 cm**

- Freely selectable light emission area due to interchangeable glass and cover plates
- Power-Select allows the adjustment of the system power 50% / 100%
- High-quality aluminum housing with powder coating in DB703
- Robust, splash-proof design for outdoor use with IP 54 protection
- Glare-free and homogeneous light distribution with high color rendering Ra>82
- EasyMount platform enables simple and fast installation
- For looping through with connection box (input and output each for 3 x 2.5 mm<sup>2</sup> cable)
- Mounting base made of special aluminum alloy, approved for installation with ground contact
- Insect-friendly lighting due to warm white LEDs

SUCCESION ARTICLE	-	BEAM ANGLE	360°
WEIGHT IN KG	1.63	PROTECTION CLASS (IP)	IP65
POWER CONSUMPTION IN WATTS	7.5-15	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	400/800	INPUT VOLTAGE	176 - 240 V AC/DC
LUMEN PER WATT	53	SERVICE LIFE	approx. 40.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRI > 82
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK06
		LUMEN PER WATT	53
		HOUSING COLOUR	gray
		WARRANTY IN YEARS	5
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC000062
		COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
		IMPACT STRENGTH	IK06
		PULSE DURATION IN µS	0
		BEG FUNDING	Only relevant in Germany
		ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	G

**Dimensions**

length: 120mm  
width: 120mm  
height: 200mm