

PRODUCT NO. 2347-1FW180

## DOTLUX LED light LUNA IP44 Ø330mm 18W COLORselect



to the product page

3 light colors in one luminaire - The right light color can be set for every application environment.

1. warm white 3.000 K: hotel, store, wellness/spa areas, home & living
  2. neutral white 4.000 K: office, gastronomy, industry, sanitary, retirement homes and hospitals
  3. daylight white 5.700 K: Industry, meeting rooms, educational institutions, Office
- Frosted cover provides shadow-free light Distribution
  - Stable PMMA plastic cover
  - Self-cooling LED module
  - Integrated luminaire connection with pressure clamp
  - Suitable for central battery
  - Sustainable, repairable product design

SUCCESSION ARTICLE 2347-2FW180  
PREDECESSOR ARTICLE 2347-0FW180

WEIGHT IN KG 0.6  
POWER CONSUMPTION IN WATTS 18  
NET LUMINOUS FLUX IN LUMENS max. 1950  
LUMEN PER WATT 108

### Dimensions

height: 95mm  
diameter: 330mm

BEAM ANGLE 180°  
PROTECTION CLASS (IP) IP44  
INPUT VOLTAGE 176 - 240 V AC/DC  
SERVICE LIFE approx. 50.000 h at 25°C  
COLOR TEMPERATURE IN KELVIN 3000/4000/5700  
COLOR-RENDERING-INDEX CRI > 82  
POWER FACTOR 0,5  
IK PROTECTION IK07  
LUMEN PER WATT 108  
PROTECTION CLASS I  
HOUSING COLOUR white  
SUITED FOR EMERGENCY LIGHTING No  
SWITCH CYCLES > 100.000  
WARRANTY IN YEARS 5  
ASSORTMENT Proline  
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 not required  
ETIM GRUPPEN-ID EC002892  
DIMMING 0-10 V No  
DIMMING 1-10 V No  
DIMMING DALI No  
DIMMING DMX No  
DIMMING DSI No  
DIMMING POTENTIOMETER (INTEGRATED) No  
DIMMING LINESWITCH No

<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>IMPACT STRENGTH</b>	IK07
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	No
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No