

PRODUCT NO. 4668

LED power supply CV 24V 120W 5A dimmable DALI/PWM IP67



to the product page

- Robust construction due to plastic housing with IP67
- DALI-capable power supply unit
- The power supply has a constant voltage output

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	PWM-120-24DA (DALI auf DALI 2)
WEIGHT IN KG	0.91
POWER CONSUMPTION IN WATTS	120

Dimensions

length: 191mm
width: 63mm
height: 38mm

PROTECTION CLASS (IP)	IP67
INPUT VOLTAGE	176 - 240 V AC/DC
OUTPUT CURRENT IN A	5
POWER FACTOR	0,96
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	90
PROTECTION CLASS	II
OUTPUT VOLTAGE	24 DC/PWM
INPUT VOLTAGE SPAN	90-305 V AC / 127-431 V DC
WARRANTY IN YEARS	2
HOUSING MATERIAL	Plastic
INPUT VOLTAGE RANGE LUMINAIRE	90-305 V AC / 127-431 V DC
ETIM GRUPPEN-ID	EC002710
DIMMING DALI	Yes
DIMMING MAINS VOLTAGE MODULATION	Yes
NO DIM FUNCTION	No
PULSE DURATION IN µS	0
CORD LENGTH	30 cm
BEG FUNDING	Only relevant in Germany