

PRODUCT NO. 4671-040140

DOTLUX LED damp-proof luminaire SIMPLY IP54 1160mm 30W 4000K IK10 DALI



to the product page

- Housing made of shatterproof polycarbonate with frosted cover for shadow-free light distribution
- 5-pole through-wiring with internal luminaire terminal block and two gaskets
- easy-to-maintain modular internal design with highest quality components
- Cable ducts on the back facilitate installation and through-wiring for surface mounting
- Silicone-free
- Sustainable product design due to easily replaceable components
- The large luminous surface made of polycarbonate produces a uniform and at the same time ceiling-brightening light distribution

WEIGHT IN KG		1.9	BEAM ANGLE		140°
POWER CONSUMPTION IN WATTS		30	PROTECTION CLASS (IP)		IP54
NET LUMINOUS FLUX IN LUMENS		3700	LIGHT COLOR		white
LUMEN PER WATT		123	INPUT VOLTAGE		176 - 240 V AC/DC
			SERVICE LIFE		approx. 50.000 h at 25°C
			COLOR TEMPERATURE IN KELVIN		4000
			COLOR-RENDERING-INDEX		CRI > 82
			POWER FACTOR		0,95
			INRUSH CURRENT IN A		0
			IK PROTECTION		IK10
			LUMEN PER WATT		123
			PROTECTION CLASS		I
			HOUSING COLOUR		white
			SUITED FOR EMERGENCY LIGHTING		yes
			SWITCH CYCLES		> 100.000
			WARRANTY IN YEARS		5
			ASSORTMENT		Proline
			ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015		not required
			ETIM GRUPPEN-ID		EC002892
			MATERIAL COVER		Plastic matt/satinized
			DIMMING DALI		Yes
			NO DIM FUNCTION		No
			COLOUR CONSISTENCY (MCADAM ELLIPSE)		SDCM6
			IMPACT STRENGTH		IK10
			SUITABLE FOR EMERGENCY LIGHTING		Yes

Dimensions

length: 1160mm
width: 109mm
height: 85mm

COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
PULSE DURATION IN μ S	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	E
COLOUR OF LIGHT ADJUSTABLE	No