

PRODUCT NO. 4561-040360

DOTLUX LED wall lamp WAY 15cm 7.5/15W 4000K



to the product page

- Freely selectable light emission area due to interchangeable glass and cover plates
- Power-Select allows setting of system power 50% / 100%
- High-quality aluminum housing with powder coating in DB703
- Robust, splash-proof design for outdoor use with IP 54 protection
- Glare-free and homogeneous light distribution with high color rendering Ra>82
- EasyMount platform enables simple and fast mounting

SUCCESION ARTICLE	-
WEIGHT IN KG	1.6
POWER CONSUMPTION IN WATTS	7.5-15
NET LUMINOUS FLUX IN LUMENS	400/800
LUMEN PER WATT	53

Dimensions

length: 120mm
width: 120mm
height: 148mm

BEAM ANGLE	360°
PROTECTION CLASS (IP)	IP65
LIGHT COLOR	white
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 40.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
INRUSH CURRENT IN A	0
IK PROTECTION	IK06
LUMEN PER WATT	53
PROTECTION CLASS	I
HOUSING COLOUR	gray
WARRANTY IN YEARS	5
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
MATERIAL COVER	Plastic, structured
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK06
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany

ENERGIEEFFIZIENZKLASSE DER
LICHTQUELLE EINER LEUCHTE
COLOUR OF LIGHT ADJUSTABLE

G

No