

PRODUCT NO. 4730-030120

**DOTLUX Wall lamp BEAMO 10W 3000K black**



to the product page

- Rugged, splash-proof design for outdoor use with IP 65 protection
- EasyBase platform enables simple and fast installation
- Two independently adjustable beam angles with angle indicators
- Special light diffuser provides sharp lighting effects with virtually no color distortion
- Particularly insect-friendly lighting due to warm white LEDs and asymmetrical light distribution

SUCCESSION ARTICLE	-	BEAM ANGLE	15° - 120°
WEIGHT IN KG	0.49	PROTECTION CLASS (IP)	IP65
POWER CONSUMPTION IN WATTS	10	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	900	INPUT VOLTAGE	220 - 240 V AC
LUMEN PER WATT	90	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,95
		INRUSH CURRENT IN A	0
		LUMEN PER WATT	90
		PROTECTION CLASS	I
		HOUSING COLOUR	black
		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	3
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002892
		MATERIAL COVER	Plastic, transparent
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No

**Dimensions**

length: 120mm  
width: 97mm  
height: 100mm

<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN <math>\mu</math>S</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	D
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No