

PRODUCT NO. 4732-0FW110

DOTLUX Tracklight STICKtrack 30W 1,2m COLORselect black



















to the product page

- One part number three light colors adjustable by COLORselect
- Natural color perception due to extra high CRI>95 value
- Compact design, ideal for low room heights
- Uniform light distribution for optimum ambient lighting
- Benefit from the large-area illumination of a light band with simple installation in your track rail

SUCCESSION ARTICLE

WEIGHT IN KG 0.76

POWER CONSUMPTION IN WATTS 30

NET LUMINOUS FLUX IN LUMENS max. 3060

LUMEN PER WATT 102

Dimensions

length: 1240mm width: 32mm height: 52mm BEAM ANGLE 110°
PROTECTION CLASS (IP) IP20

 LIGHT COLOR
 multicoloured

 INPUT VOLTAGE
 176 - 240 V AC/DC

 SERVICE LIFE
 approx. 50.000 h at 25°C

 COLOR TEMPERATURE IN KELVIN
 3000/4000/5700

COLOR-RENDERING-INDEX CRI > 95 POWER FACTOR 0,9 **INRUSH CURRENT IN A** 0 **LUMEN PER WATT** 102 PROTECTION CLASS HOUSING COLOUR black SUITED FOR EMERGENCY LIGHTING yes WARRANTY IN YEARS 7 **SIMILAR TO RAL-COLOUR** 9005

ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION

2019/2015

ASSORTMENT

(INTEGRATED)

ETIM GRUPPEN-ID EC001744

MATERIAL COVER Plastic matt/satinized

Proline

not required

DIMMING 0-10 V No
DIMMING 1-10 V No
DIMMING DALI No
DIMMING DMX No
DIMMING DSI NO
DIMMING POTENTIOMETER



DIMMING LINESWITCH No **DIMMING MANUFACTURER'S** No PROPRIETARY SYSTEM DIMMING MAINS VOLTAGE No MODULATION **DIMMING PHASE CUT-OFF** No **DIMMING PROGRAMMABLE** No DIMMING RF No DIMMING SINE WAVE REDUCTION No DIMMING TOUCH AND DIM No DIMMING ZIGBEE No DIMMING WITH PUSH-BUTTON No DIMMING DEPENDING ON CONTROL No **GEAR** NO DIM FUNCTION Yes **COLOUR CONSISTENCY (MCADAM** SDCM6 **ELLIPSE)** SUITABLE FOR EMERGENCY LIGHTING Yes **DIMMING DALI-2** No **DIMMING PHASE CUT-ON** No **DIMMING GPRS** No PULSE DURATION IN µS 0 **BEG FUNDING** Only relevant in Germany **ENERGIEEFFIZIENZKLASSE DER** LICHTQUELLE EINER LEUCHTE

No

COLOUR OF LIGHT ADJUSTABLE