

PRODUCT NO. 4733-OFW110

**DOTLUX Tracklight STICKtrack 30W 1,2m COLORselect white**



to the product page

- One part number - three light colors adjustable by COLORselect
- Natural color perception due to extra high CRI>95 value
- Compact design, ideal for low room heights
- Uniform light distribution for optimum ambient lighting
- Benefit from the large-area illumination of a light band with simple installation in your track rail

SUCCESSION ARTICLE	-
WEIGHT IN KG	0.718
POWER CONSUMPTION IN WATTS	30
NET LUMINOUS FLUX IN LUMENS	max. 3060
LUMEN PER WATT	102

Dimensions

length: 1240mm  
width: 32mm  
height: 52mm

BEAM ANGLE	110°
PROTECTION CLASS (IP)	IP20
LIGHT COLOR	multicoloured
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
COLOR-RENDERING-INDEX	CRI > 95
POWER FACTOR	0,9
INRUSH CURRENT IN A	0
LUMEN PER WATT	102
PROTECTION CLASS	I
HOUSING COLOUR	white
SUITED FOR EMERGENCY LIGHTING	yes
WARRANTY IN YEARS	3
SIMILAR TO RAL-COLOUR	9016
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC001744
MATERIAL COVER	Plastic matt/satinized
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No

<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	Yes
<b>COLOUR OF LIGHT ADJUSTABLE</b>	Positions
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN µS</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	F