


PRODUCT NO. 4777-040120

DOTLUX LED damp-proof luminaire HIGHFORCEabs IP66/IP69 1455mm 54W 4000K IK06 1x3-pole



to the product page

- UV-stable diffuser and housing
- Chemical-resistant special diffuser made of ChemRST material
- Suitable for agricultural use
- Housing made of impact resistant polycarbonate
- Impact resistance IK06
- Suitable for central battery
- IP66 / IP69
- D-certified
- DLG certified
- Distance between both mounting brackets adjustable (700-980mm)
- Mounting brackets allow ceiling and/or wall mounting
- All HIGHFORCE lights are delivered without connector plug. Accessories can be found here in the store.

WEIGHT IN KG		1.65	BEAM ANGLE		120°
POWER CONSUMPTION IN WATTS		54	PROTECTION CLASS (IP)		other IP66 / IP69
NET LUMINOUS FLUX IN LUMENS		7170	LIGHT COLOR		white
LUMEN PER WATT		133	INPUT VOLTAGE		176 - 240 V AC/DC
			SERVICE LIFE		approx. 50.000 h at 25°C
			COLOR TEMPERATURE IN KELVIN		4000
			COLOR-RENDERING-INDEX		CRI > 82
			POWER FACTOR		0,95
Dimensions			INRUSH CURRENT IN A		0
length: 1455mm			IK PROTECTION		IK06
width: 90mm			LUMEN PER WATT		133
height: 99mm			PROTECTION CLASS		I
			HOUSING COLOUR		gray
			SUITED FOR EMERGENCY LIGHTING		yes
			FOOD-READY		Yes
			WARRANTY IN YEARS		7
			ASSORTMENT		Highline
			ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015		not required
			ETIM GRUPPEN-ID		EC002892
			DIMMING 0-10 V		No
			DIMMING 1-10 V		No
			DIMMING DALI		No
			DIMMING DMX		No
			DIMMING DSI		No
			DIMMING POTENTIOMETER (INTEGRATED)		No

DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK06
SUITABLE FOR EMERGENCY LIGHTING	Yes
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	D
COLOUR OF LIGHT ADJUSTABLE	No