

PRODUCT NO. 4694-900

Lichtmanagementsystem HCL-Netzteil 30W 900mA DALI DT8 dimmbar



to the product page

- Intelligentes und DALI dimmbares 2-Kanal Vorschaltgerät - Zwei individuell steuerbare Ausgangskanäle
- DALI DT8 Version für Tunable White oder HCL Anwendungen - SELV Ausgangsspannung - Zentralbatteriegeeignet - Flicker-Free - Von 1 - 100% dimmbar - Push-Dim Funktion - Schutz vor abnormalen Betriebszuständen, wie Kurzschluss, unterbrochener Lastkreis oder Überlast

SUCCESSION ARTICLE	4934-950
PREDECESSOR ARTICLE	4184-900
WEIGHT IN KG	0
POWER CONSUMPTION IN WATTS	30
CONSUMPTION (KWH/1000H)	30

Dimensions

length: 210mm
width: 95mm
height: 50mm

INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h bei T _{c,max} = 75°C
FREQUENCY RANGE IN HZ	50/60
OUTPUT CURRENT IN A	0,9
MINIMUM LOAD IN WATT	2,5
OUTPUT OF POWER SUPPLY UNIT	30 W
TC TEMPERATURE IN °C	75
SWITCH CYCLES	> 100.000
INPUT VOLTAGE SPAN	198-264 V AC
HOUSING MATERIAL	Steel
STAND BY LOSSES	< 0,5 W
INPUT VOLTAGE RANGE LUMINAIRE	198-264 V AC
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002710
DIMMING DALI	Yes
DIMMING WITH PUSH-BUTTON	Yes