



PRODUCT NO. 2805-045120

## DOTLUX QUICK-FIX LED exchangeable module Ø15cm 15W 4500K



to the product page

- Universal MAGNET LED module with integrated driver for quick and easy replacement of light sources in existing ceiling and wall luminaires
- Extra high magnetic feet enable installation above the existing cabling
- Very high efficiency of up to 120lm/W



SUCCESSION ARTICLE -  
PREDECESSOR ARTICLE 2805-001

WEIGHT IN KG 0.11  
POWER CONSUMPTION IN WATTS 15  
NET LUMINOUS FLUX IN LUMENS 1800  
LUMEN PER WATT 120

### Dimensions

height: 32mm  
diameter: 150mm

BEAM ANGLE 120°  
PROTECTION CLASS (IP) IP20  
INPUT VOLTAGE 220 - 240 V AC  
SERVICE LIFE approx. 20.000 h at 25°C  
COLOR TEMPERATURE IN KELVIN 4500  
COLOR-RENDERING-INDEX CRI > 82  
POWER FACTOR 0,57  
LUMEN PER WATT 120  
PROTECTION CLASS II  
VOLTAGE TYPE AC  
SWITCH CYCLES > 40.000  
INPUT VOLTAGE SPAN 185-264 V AC  
WARRANTY IN YEARS 2  
L80/B10 10000  
DIMMING WITHOUT DIMMER No  
INPUT VOLTAGE RANGE LUMINAIRE 185-264 V AC  
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 D  
LIFETIME L80/B10 AT 25°C 10000  
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C 20000  
LIFETIME L80/B20 AT 25°C 0  
ETIM GRUPPEN-ID EC000996  
NO DIM FUNCTION Yes  
COLOUR CONSISTENCY (MCADAM ELLIPSE) SDCM6  
CONNECTION TYPE Cable

<b>PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471</b>	RG1
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>FLEXIBLE</b>	Nein
<b>SUITABLE FOR TRAFFIC LIGHTS</b>	No
<b>EXTERNAL DRIVER REQUIRED</b>	Yes
<b>SUITABLE FOR CONSTANT VOLTAGE</b>	No
<b>SUITABLE FOR GENERAL LIGHTING</b>	Yes
<b>SUITABLE FOR CONSTANT CURRENT</b>	Yes
<b>SUITABLE FOR RAIL TRAFFIC</b>	No
<b>SUITABLE FOR MATRIX INFORMATION BOARDS</b>	No
<b>SUITABLE FOR VARIABLE ROAD SIGNS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	20000
<b>LIFETIME L90/B10 AT 25°C</b>	5000
<b>LIGHT COLOUR ACCORDING TO EN 12464-1</b>	neutral white 3300 to 5300 K
<b>LIFETIME L90/B50 AT 25°C</b>	7000
<b>BEG FUNDING</b>	Only relevant in Germany
<b>LED-BETRIEBSSTROM IN MA</b>	150
<b>SHAPE</b>	Round
<b>COLOUR</b>	White