

PRODUCT NO. 4516-1

DOTLUX TRUEcolor tester



to the product page

Inspire your customers on site with vibrant and high-contrast colors. With TRUE-COLOR technology from DOTLUX, you can showcase products simply and authentically.

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	other
WEIGHT IN KG	0.15	COLOR TEMPERATURE IN KELVIN	3000/4000/5700
Dimensions		POWER FACTOR	0,9
		PROTECTION CLASS	none
		VOLTAGE TYPE	DC
		L80/B10	0
		DIMMING WITHOUT DIMMER	No
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	-
		LIFETIME L80/B10 AT 25°C	0
		LIFETIME L80/B20 AT 25°C	0
		ETIM GRUPPEN-ID	EC000996
		NO DIM FUNCTION	Yes
		COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
		CONNECTION TYPE	Cable
		COMPATIBLE WITH APPLE HOMEKIT	No
		COMPATIBLE WITH GOOGLE ASSISTANT	No
		COMPATIBLE WITH AMAZON ALEXA	No
		IFTTT SUPPORT AVAILABLE	No
		FLEXIBLE	Nein
		SUITABLE FOR TRAFFIC LIGHTS	No
		EXTERNAL DRIVER REQUIRED	Yes
		SUITABLE FOR CONSTANT VOLTAGE	Yes
		SUITABLE FOR GENERAL LIGHTING	Yes

SUITABLE FOR CONSTANT CURRENT	No
SUITABLE FOR RAIL TRAFFIC	No
SUITABLE FOR MATRIX INFORMATION BOARDS	No
SUITABLE FOR VARIABLE ROAD SIGNS	No
LIFETIME L90/B10 AT 25°C	0
LIGHT COLOUR ACCORDING TO EN 12464-1	neutral white 3300 to 5300 K
LIFETIME L90/B50 AT 25°C	0
BEG FUNDING	Only relevant in Germany
LED-BETRIEBSSTROM IN MA	300
SHAPE	Rectangular
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	Other
COLOUR	White