

PRODUCT NO. 4331-140240

**DOTLUX LED table lamp STUDIodesk 80W 4000K dimmable**



to the product page

- Aluminum housing in RAL9006 from the "STUDIO" series
- Integrated presence sensor activates/dims the light to 30% brightness after 10 minutes to 30% brightness and deactivates the luminaire after a further 10 minutes
- Glare-free, homogeneous and shadow-free light distribution / smooth top surface
- Better contrast rendition with very good color rendition and constant color temperature (3-step MacAdam binning)
- 1.5 m connection cable
- Emergency power capable
- Flicker-free light rendition ensures optimum vision and is easy on the eyes for fatigue-free working and creates a pleasant atmosphere in offices, meeting rooms and hotels, conference rooms and hotels.

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	4331-040240
WEIGHT IN KG	7
POWER CONSUMPTION IN WATTS	80
NET LUMINOUS FLUX IN LUMENS	8800
LUMEN PER WATT	110

Dimensions

length: 610mm  
width: 310mm  
height: 1200mm

BEAM ANGLE	120°/120°
LIGHT COLOR	white
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,95
INRUSH CURRENT IN A	0
BATTERY RUNTIME	-
LUMEN PER WATT	110
PROTECTION CLASS	I
VOLTAGE TYPE	AC
SUITED FOR EMERGENCY LIGHTING	yes
GLARE-FREE	UGR < 19
SWITCH CYCLES	> 100.000
INPUT VOLTAGE SPAN	100 -277 V AC/DC
WARRANTY IN YEARS	7
L80/B10	50000
SIMILAR TO RAL-COLOUR	9006
DIMMING WITHOUT DIMMER	No
ENABLED LICENSED PRODUCT	Yes
INPUT VOLTAGE RANGE LUMINAIRE	100 -277 V AC/DC
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	50000

LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
ETIM GRUPPEN-ID	EC000300
WITH ILLUMINANT	Yes
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	Yes
SUITABLE FOR NUMBER OF LIGHT SOURCES	1
LAMP HOLDER	-
MATERIAL COVER	Plastic matt/satinized
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	Yes
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	Yes
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	No
LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM3
SUITABLE FOR EMERGENCY LIGHTING	Yes
WITH MOVEMENT SENSOR	Yes
WITH LIGHT SENSOR	No
CONSTANT LIGHT OUTPUT (CLO)	Yes
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
ELECTRICAL CONNECTION WITH CONNECTOR SYSTEM	No
LUMINAIRE HEADS FLEXIBLE	No
DIRECT-/INDIRECT PROPORTION SEPARATELY CONTROLLABLE	Yes
ADJUSTABLE	Nein
EXCHANGEABLE CONTROL GEAR	Yes
SUITABLE FOR LAMP POWER IN W	-
LAMP TYPE	LED
WITH DIMMER	No
WITH PRESENCE INDICATOR	No

<b>WITH REFLECTOR</b>	No
<b>WITH SWITCH</b>	No
<b>WITH SEPARATE READING LIGHT</b>	No
<b>MATERIAL</b>	Aluminium
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	100000
<b>LIFETIME L90/B10 AT 25°C</b>	25000
<b>PULSE DURATION IN µS</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	-
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>LIGHT SHARING</b>	Symmetric
<b>LIGHT OUTLET</b>	Direct/indirect
<b>LUMINOUS FLUX ADJUSTABLE</b>	Continuously variable
<b>TYPE OF GRID</b>	None
<b>HOUSING COLOUR</b>	silver