

PRODUCT NO. 4866-050015

DOTLUX LED floodlight LENSplus 150W 5000K 15° beam angle



to the product page

Wide variety of different beam angles enables optimum illumination for every situation

- Reliable operation thanks to highly efficient Lumileds® LEDs with 3-step MacAdam binning
- Solid, waterproof, ADC12 die-cast aluminum housing with pressure equalization valve (IP 66/IK08) and high-quality powder coating from Akzo Nobel
- ESG \“ULTRA CLEAR\” highly transparent glass for excellent light color and improved light output
- Durable industrial power supply with 10kV overvoltage protection
- Curved mounting bracket allows easy mounting without disassembling the bracket (freely rotatable 320°)
- Incl. 1.5m UV-stable rubber cable (H05RN-F open ends)
- Replaceable components therefore repairable
- Sustainable product design due to easily replaceable components

WEIGHT IN KG		4.5	BEAM ANGLE		15°
POWER CONSUMPTION IN WATTS		150	PROTECTION CLASS (IP)		IP66
NET LUMINOUS FLUX IN LUMENS		18700	LIGHT COLOR		white
LUMEN PER WATT		125	INPUT VOLTAGE		176 - 240 V AC/DC
			SERVICE LIFE		approx. 50.000 h at 25°C
			COLOR TEMPERATURE IN KELVIN		5000
			COLOR-RENDERING-INDEX		CRI > 82
			POWER FACTOR		0,98
Dimensions			INRUSH CURRENT IN A		0
length: 375mm			IK PROTECTION		IK08
width: 320mm			LUMEN PER WATT		125
height: 75mm			PROTECTION CLASS		I
			VOLTAGE TYPE		AC/DC
			HOUSING COLOUR		black
			SUITED FOR EMERGENCY LIGHTING		No
			SWITCH CYCLES		> 100.000
			OVERVOLTAGE PROTECTION		up to 10000 V
			WARRANTY IN YEARS		7
			L80/B10		50000
			SUITABLE FOR SURFACE MOUNTING		Yes
			SUITABLE FOR MOUNTING		No
			DIMMING WITHOUT DIMMER		No
			ASSORTMENT		Highline
			ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015		not required
			LIFETIME L80/B10 AT 25°C		50000

LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
ETIM GRUPPEN-ID	EC001744
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	Yes
LAMP HOLDER	-
MATERIAL COVER	Glass transparent
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	No
LIGHT DISTRIBUTOR	Focal lens
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK08
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	Yes
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
CONSTANT LIGHT OUTPUT (CLO)	No
TYPE OF WIRING	Ending
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR LOW VOLTAGE CABLE SYSTEM	No
SUITABLE FOR CLAMP-MOUNTING	Yes
SUITABLE FOR LIGHT-TRACK MOUNTING	No

SUITABLE FOR PEDESTAL/FLOOR MOUNTING	Yes
SUITABLE FOR TRAVERSE MOUNTING	Yes
EXCHANGEABLE CONTROL GEAR	No
LAMP TYPE	LED
EMERGENCY POWER SUPPLY INTEGRATED	No
SURFACE BRUSHED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
PULSE DURATION IN µS	0
LIFETIME L90/B50 AT 25°C	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	D
LIGHT OUTLET	Direct
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
LIGHT SHARING	Symmetric
ADJUSTABILITY	Swivelling
SURFACE PROTECTION	Powder coating
CONNECTION TYPE	Other