

PRODUCT NO. 4892-040036

DOTLUX LED tracklight SLIMtrack-eco 25W 4000K white







to the product page

- EDISON® brand LED and flicker-free power supply unit
- Excellent price-performance ratio
- Natural color perception due to extra high CRI value
- Die-cast aluminum housing
- Passive cooling system without fan

SUCCESSION ARTICLE	4891-199036	BEAM ANGLE	36°
		PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.76	LIGHT COLOR	white
POWER CONSUMPTION IN WATTS	25	INPUT VOLTAGE	220 - 240 V AC
NET LUMINOUS FLUX IN LUMENS	2500	SERVICE LIFE	approx. 50.000 h at 25°C
LUMEN PER WATT	100	COLOR TEMPERATURE IN KELVIN	4000
		COLOR-RENDERING-INDEX	CRI > 92
		POWER FACTOR	0,97
		INRUSH CURRENT IN A	0
Dimensions		LUMEN PER WATT	100
		PROTECTION CLASS	I
length: 280mm		HOUSING COLOUR	white
diameter: 85mm		SWITCH CYCLES	> 100.000
		OVERVOLTAGE PROTECTION	1500 V
		WARRANTY IN YEARS	З
		ASSORTMENT	Ecoline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC001744
		MATERIAL COVER	Plastic matt/satinized
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No



DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
NO DIM FUNCTION COLOUR CONSISTENCY (MCADAM ELLIPSE)	Yes SDCM6
COLOUR CONSISTENCY (MCADAM	
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
COLOUR CONSISTENCY (MCADAM ELLIPSE) DIMMING DALI-2	SDCM6
COLOUR CONSISTENCY (MCADAM ELLIPSE) DIMMING DALI-2 DIMMING PHASE CUT-ON	SDCM6 No No
COLOUR CONSISTENCY (MCADAM ELLIPSE) DIMMING DALI-2 DIMMING PHASE CUT-ON DIMMING GPRS	SDCM6 No No No
COLOUR CONSISTENCY (MCADAM ELLIPSE) DIMMING DALI-2 DIMMING PHASE CUT-ON DIMMING GPRS PULSE DURATION IN µS	SDCM6 No No O
COLOUR CONSISTENCY (MCADAM ELLIPSE) DIMMING DALI-2 DIMMING PHASE CUT-ON DIMMING GPRS PULSE DURATION IN µS BEG FUNDING	SDCM6 No No O Olly relevant in Germany
COLOUR CONSISTENCY (MCADAM ELLIPSE) DIMMING DALI-2 DIMMING PHASE CUT-ON DIMMING GPRS PULSE DURATION IN µS BEG FUNDING DREH- /SCHWENKBAR ENERGIEEFFIZIENZKLASSE DER	SDCM6 No No O Only relevant in Germany 350° / 90°
COLOUR CONSISTENCY (MCADAM ELLIPSE) DIMMING DALI-2 DIMMING PHASE CUT-ON DIMMING GPRS PULSE DURATION IN µS BEG FUNDING DREH- /SCHWENKBAR ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	SDCM6 No No O Only relevant in Germany 350° / 90° E