

## **PRODUCT NO.** 4897-050090

## DOTLUX LED indoor floodlight LIGHTSHOWERsmart 80-150W 5000K






















to the product page



- Glare-reduced high-bay spotlight thanks to ring lens
- Additional savings potential through optional retrofittable daylight/motion sensors, programmable via infrared remote control
- POWERselect in combination with sensors adjustable via remote control (70%, 80%, 90%,100%)
- 1-10V dimmable, with optional converter Art.5078 also DALI-capable
- Optimal light output even at high altitudes due to already installed 90° ring lens
- Corrosion protected by powder-coated, robust aluminum housing IP65/IK10
- Integrated pressure compensation valve extends the service life of the seals and prevents condensation in the luminaire
- D-certified for use in fire hazardous locations suitable according to DIN EN 60598-2-24, VDE 0711-2-24
- Suitable for use in food processing plants (IFS and BRC)
- Sustainable product design due to easily replaceable components

SUCCESSION ARTICLE	5370-150090	BEAM ANGLE	90°
		PROTECTION CLASS (IP)	IP65
WEIGHT IN KG	3.8	INPUT VOLTAGE	176 - 240 V AC/DC
POWER CONSUMPTION IN WATTS	80-150	SERVICE LIFE	approx. 50.000 h at 25°C
NET LUMINOUS FLUX IN LUMENS	max. 21000	COLOR TEMPERATURE IN KELVIN	5000
LUMEN PER WATT	140	COLOR-RENDERING-INDEX	CRI > 82
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK10
		LUMEN PER WATT	140
Dimensions		PROTECTION CLASS	1
		HOUSING COLOUR	black
height: 199mm		FOOD-READY	Yes
diameter: 320mm		WARRANTY IN YEARS	5
		SIMILAR TO RAL-COLOUR	7021
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC001744
		SUITABLE FOR WALL MOUNTING	Yes
		DIMMING 1-10 V	Yes
		COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
		IMPACT STRENGTH	IK10
		LUMINOUS FLUX ADJUSTABLE	Positions

INTEGRATED

**EMERGENCY POWER SUPPLY** 

PULSE DURATION IN µS

Yes



**BEG FUNDING** 

only relevant in Germany