

PRODUCT NO. 4931-0FW120

**DOTLUX LED surface mounted luminaire SURFACEdali Ø400x62 30W 3000/4000/5700K
COLORselect white**



to the product page

- DALI dimmable version
- Quick and easy mounting with EASYbase base plate and twistlock fastener
- Large product variety allows use in all projects (e.g. sensor, exit, DALI ...)
- Sustainable design, LED module and power supply can be exchanged without tools
- Rear and side cable entry with large cable storage space allow flexible use on site
- Ideal for residential projects due to impact resistant polycarbonate housing IK10
- Modern, clear design with indirect light component
- Splash-proof housing for outdoor, wet room and indoor use
- Individual light color adjustable by COLORselect (light color: 3,000 K / 4,000 K / 5,700 K)
- Suitable for central battery
- The large luminous surface made of polycarbonate creates a uniform and at the same time ceiling-brightening light distribution
- Flexible cable entry possible at the rear and side

WEIGHT IN KG	1.6
NET LUMINOUS FLUX IN LUMENS	2850-3000
POWER CONSUMPTION IN WATTS	30
LUMEN PER WATT	max. 100

Dimensions

height: 62mm
diameter: 400mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP54
LIGHT COLOR	multicoloured
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,97
INRUSH CURRENT IN A	0
IK PROTECTION	IK10
LUMEN PER WATT	max. 100
PROTECTION CLASS	II
VOLTAGE TYPE	AC
HOUSING COLOUR	white
WARRANTY IN YEARS	5
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
MATERIAL COVER	Plastic matt/satinized
DIMMING DALI	Yes
NO DIM FUNCTION	No
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK10

COLOUR OF LIGHT ADJUSTABLE

PULSE DURATION IN μ S

BEG FUNDING

ENERGIEEFFIZIENZKLASSE DER
LICHTQUELLE EINER LEUCHTE

Positions

0

Only relevant in Germany

C