

PRODUCT NO. 4934-500

Light management system LED power supply unit 38Watt 500mA DALI DT8 dimmable



to the product page

- Independent dimmable two-channel DALI DT8 LED driver
- Dimming range from 1 - 100% with amplitude dimming
- Suitable for DC input voltage and emergency lighting systems in accordance with EN50172
- Strain relief with the option of through-wiring
- colorSWITCH - setting the color temperature via push-button
- Tunable White applications

SUCCESSION ARTICLE -  
PREDECESSOR ARTICLE 4184-500

WEIGHT IN KG 0.241

Dimensions

length: 215mm  
width: 70mm  
height: 31mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	176 - 240 V AC/DC
Service life	
OUTPUT CURRENT IN A	0,5
MINIMUM LOAD IN WATT	7
OUTPUT OF POWER SUPPLY UNIT	38 W
INRUSH CURRENT IN A	26.4
TC TEMPERATURE IN °C	75
OUTPUT VOLTAGE	20 - 50 DC
INPUT VOLTAGE SPAN	198-264 V AC
HOUSING MATERIAL	Polycarbonate
STAND BY LOSSES	< 0,25 W
INPUT VOLTAGE RANGE LUMINAIRE	198-264 V AC
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002710
DIMMING DALI	Yes
NO DIM FUNCTION	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
PULSE DURATION IN µS	224
CORD LENGTH	20 cm
BEG FUNDING	Only relevant in Germany