

PRODUCT NO. 4941-350

Light management system LED power supply unit 38Watt 350mA CASAMBI dimmable



to the product page

- Independent dimmable dual-channel CASAMBI LED driver
- Automatically establishes a wireless communication network with up to 127 nodes
- Dimming range from 1 - 100% with amplitude dimming
- Suitable for DC input voltage and emergency lighting systems in accordance with EN50172
- Strain relief with the option of through-wiring
- Tunable White applications

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.22	INPUT VOLTAGE	176 - 240 V AC/DC
		Service life	
		OUTPUT CURRENT IN A	0,35
		MINIMUM LOAD IN WATT	7
		OUTPUT OF POWER SUPPLY UNIT	38 W
		INRUSH CURRENT IN A	26.4
		TC TEMPERATURE IN °C	75
		OUTPUT VOLTAGE	20 - 50 DC
		INPUT VOLTAGE SPAN	198-264 V AC
		HOUSING MATERIAL	Polycarbonate
		STAND BY LOSSES	< 0,37 W
		INPUT VOLTAGE RANGE LUMINAIRE	198-264 V AC
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002710
		COMPATIBLE WITH APPLE HOMEKIT	No
		COMPATIBLE WITH GOOGLE ASSISTANT	No
		COMPATIBLE WITH AMAZON ALEXA	No
		IFTTT SUPPORT AVAILABLE	No
		PULSE DURATION IN µS	224
		CORD LENGTH	20 cm
		BEG FUNDING	Only relevant in Germany