

PRODUCT NO. 4941-950

Light management system LED power supply unit 38Watt 950mA CASAMBI dimmable



to the product page

- Independent dimmable dual-channel CASAMBI LED driver
- Automatically establishes a wireless communication network with up to 127 nodes
- Dimming range from 1 - 100% with amplitude dimming
- Suitable for DC input voltage and emergency lighting systems in accordance with EN50172
- Strain relief with the option of through-wiring
- Tunable White applications

SUCCESSION ARTICLE	-
WEIGHT IN KG	0.25

Dimensions

length: 215mm
width: 70mm
height: 31mm
diameter: 75mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	176 - 240 V AC/DC
Service life	
OUTPUT CURRENT IN A	0,95
INRUSH CURRENT IN A	26.4
TC TEMPERATURE IN °C	75
OUTPUT VOLTAGE	20 - 40 DC
INPUT VOLTAGE SPAN	198-264 V AC
INPUT VOLTAGE RANGE LUMINAIRE	198-264 V AC
ETIM GRUPPEN-ID	EC002710
NO DIM FUNCTION	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
PULSE DURATION IN µS	224
BEG FUNDING	Only relevant in Germany