

PRODUCT NO. 4942-050160

DOTLUX LED-Lichtbandsystem LINEAcompact 50W breitstrahlend 1452mm 5000K nicht dimmbar



to the product page

WEIGHT IN KG	0
POWER CONSUMPTION IN WATTS	50
CONSUMPTION (KWH/1000H)	50
NET LUMINOUS FLUX IN LUMENS	8500

Dimensions

length: 1452mm
width: 66mm
height: 63mm

BEAM ANGLE	160°
PROTECTION CLASS (IP)	IP54
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	5000
POWER SUPPLY	Internal
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,98
INRUSH CURRENT IN A	0
PROTECTION CLASS	I
VOLTAGE TYPE	AC
SWITCH CYCLES	> 100.000
COVER MATERIAL	Polycarbonate PC
HOUSING MATERIAL	Aluminium
L/B VALUE	L80/B10
ETIM GRUPPEN-ID	EC002892
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No

DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
OPTICS OF THE COVER	frosted