

PRODUCT NO. 4966-030120

DOTLUX LED solar bollard light FLASHground with sensor 100 cm 3.5W 3000K



to the product page

- Solar lithium-ion battery light with motion sensor (2 selectable modes)
- Reliable and fast battery charging due to large SOLAR panel, also suitable for indirect light incidence
- Particularly insect-friendly lighting due to warm white LEDs and motion sensor
- High-quality, splash-proof aluminum housing with weather-resistant powder coating
- Large homogeneously designed light area enables glare-free light distribution
- Includes rechargeable battery (replaceable) and mounting accessories
- Concrete anchor optionally available Article no.: 4968

Operating modes Motion sensor:

A) 15% permanent light intensity after sunset , 100% light intensity when motion (duration 15 seconds).

B) 0% light intensity after sunset, 100% light intensity in case of movement (duration 15 seconds)

SUCCESSION ARTICLE	-	BEAM ANGLE	120°
WEIGHT IN KG	3.9	PROTECTION CLASS (IP)	IP54
POWER CONSUMPTION IN WATTS	3,5	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	250	SERVICE LIFE	approx. 30.000 h at 25°C
LUMEN PER WATT	71	COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRI > 82
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK06
		BATTERY RUNTIME	3h at 100% / 20h at 15%
Dimensions		LUMEN PER WATT	71
length: 148mm		PROTECTION CLASS	III
width: 220mm		HOUSING COLOUR	gray
height: 1000mm		WARRANTY IN YEARS	3
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC000062
		MATERIAL COVER	Plastic matt/satinized
		NO DIM FUNCTION	Yes
		COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
		IMPACT STRENGTH	IK06
		LAMP TYPE	LED
		PULSE DURATION IN µS	0
		BEG FUNDING	Only relevant in Germany
		ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	-